

# TR156-85A

15.6" Intel® Core™ 8th i3/i5/i7 Processor  
Industrial Panel PC



## Features:

- Intel® Core™ 8th i3/i5/i7 processor
- Industrial display, multi-point capacitor touch screen
- Onboard 8GB LPDDR3 memory
- 3\*USB3.0, 1\*USB2.0, 4\*RS232
- 1\*HD 1.4A, support 1080P@60Hz output, 1\*VGA
- 2\* Intel® Gigabit LAN, 1 of which supports Wake-on-LAN
- Fanless design
- Panel protection level can reach IP65



## Specifications:

### System Hardware

CPU	Intel® Core™ i5-8265u (optional i3-8145U /i7-8565U)	Watchdog	Support hardware reset function (256 levels, 0~255 seconds)
Memory	Board 8GB LPDDR3 memory	Storage	M.2, 128GB, up to 512GB

### Display

LCD Type	15.6" LCD	Luminance	450 cd/m <sup>2</sup>
Touchscreen Type	Capacitive touch screen	Contrast Ratio	800: 1
Max. Resolution	1920*1080		

### OS

OS	Windows10、Linux
----	-----------------

### I/O Ports

USB	3*USB3.0 +1*USB2.0	Mini PCIe	1*mini pcie (wifi/bt/4G/5G optional)
Serial Port	4*RS232 (2*RS485 optional)	SIM card	1* Built-in SIM card seat
Network Port	2* RJ45 Gigabit network interface	M.2	1*M.2 NVME SLOT(2280)
Audio	1*Line-out+1*Mic-in	Expansion port	PCIEX1/SMBUS/USB2.0X1/UART X2
Video	1*HD+1*VGA		
DC Port	Phoenix terminal 3pin		

### Power

Power	12V~ 28V wide pressure input (1*3pin phoenix terminal), standard 19V/4.74A adapter (extended POE module optional adapter)
-------	---

## Environment

Vibration Protection	5-17Hz/1.0mm amplitude; 17-200Hz/1.0g acceleration	Operating Temp.	-10°C~55°C (wide temperature optional)
Shock Protection	10g acceleration, 11ms cycle	Storage Temp.	-30°C~70°C (wide temperature optional)
IP Rating	Front panel IP65	Humidity	95% @40°C, non-condensing

## Mechanical

Dimension (WxHxD)	408*257.3*69.9mm	Material	Aluminum alloy
Weight	4.3kg	Mounting	VESA mounting: 100*100mm
Color	Silver		Embedded installation: 393.4*242.6mm

## Dimensions:

